



CJC™ Off-line Fine Filter Insert

A 38/20 (38/40 - 38/60 - 38/80 - 38/100)

APPLICATION

The type A filter insert is ideal for the fine filtration of mineral and synthetic based

Engine lube oils
Turbine lube oils
Hydraulic oils
Gear oils
Honing oils
Quenching oils

FILTRATION CAPABILITY

All CJC™ Filter Inserts have a filtration degree of 3 µm (micron) absolute (equiv. to 0.8 µm nominal) i.e. 98.7 % of all solid particles >3 µm and approx. 50 % of all particles >0.8 µm are retained in each pass.

The dirt holding capacity of an A 38/20 insert is 2.5 litres of evenly distributed solids.

The water absorption potential is up to 50% (i.e. 1,250 mL H₂O) of the total contaminant holding capacity.

COMPONENTS

CJC™ type A Fine Filter Inserts consists of bonded discs made from:

Wood cellulose
Polyamin
Antifoam
Cellulose glue



DIMENSIONS

The figures below are nominal:

<i>Sizes</i>	<i>Figures</i>		
	<i>Diameter</i>	<i>Height</i>	<i>Weight (dry)</i>
<i>38/20</i>	<i>38 cm</i>	<i>20 cm</i>	<i>5 kg</i>
<i>38/40</i>	<i>38 cm</i>	<i>40 cm</i>	<i>10 kg</i>
<i>38/60</i>	<i>38 cm</i>	<i>60 cm</i>	<i>15 kg</i>
<i>38/80</i>	<i>38 cm</i>	<i>80 cm</i>	<i>20 kg</i>
<i>38/100</i>	<i>38 cm</i>	<i>100 cm</i>	<i>25 kg</i>



C.C.JENSEN

C.C.JENSEN A/S * Løvholmen 13 * DK-5700 Svendborg * Denmark

Phone: +45 63 21 20 14* Fax: +45 62 22 46 15

Email: filter@cjc.dk * Web: www.cjc.dk



Distributor

Oil Solutions

Phone 0421 336 009
Fax 03 9012 4332

International

Phone 61 421 336 009
Fax 61 3 9012 4332

sales@oilsolutions.com.au
www.oilsolutions.com.au

PO Box 653 Castlemaine Australia 3450

